



IMPRESSIONS™

Brilliant Gloss / Ultra Wear Floor Finish

DESCRIPTION

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

PRODUCT FEATURES / BENEFITS

- Very hard wear surface / Extremely scuff resistant
- Enhanced leveling; repairs easily / Usable by any personnel in many applications
- Super brilliant gloss / Maximizes appearance & user appeal
- Fast drying / Allows faster re-coating and less waiting
- Pure thermoplastic polymers / Very responsive to multi-speed polishing

DIRECTIONS FOR USE

Floor Preparation: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly with clean water and allow to completely dry. Application: If desired one or two coats of an approved sealer may be used, prior to finish application. Using a clean mop or applicator apply a thin uniform coat of finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area. Spray Buff: To restore original luster, polish with an approved spray buff compound or laminator.

High Speed Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. The floor should first be damp mopped with a suitable neutral cleaner and allowed to dry. The surface may then, as desired, be dry burnished with a high speed white or tan buffing pad, or using the same equipment, be spray buffed using an

approved product. An alternate method, for insuring a long lasting durable surface, would be to apply an approved mop-on restorer or laminator, allow to dry and then to follow the dry buffing procedure. Floor finish can also be polished by auto scrub method.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

SPECIFICATIONS

Type	Pure acrylic polymers
pH	8.2 ± 0.3
Drying Time (minutes)	20-30
Color	White, opaque liquid
Odor	Acrylic
Film Appearance	Clear
Powdering	None
Flash Point	None
Freeze thaw stable	Yes (3 Freeze Thaw Cycles)
Detergent Resistant	Yes

Multi-Speed Buffing	Yes
Leveling	Excellent
Black Mark Resistant	Superior
Scuff Resistance	Superior
Soil Resistance	Superior
Durability	Excellent
Recoatibility	Excellent
Removability	Excellent
Immediate Wet Look Gloss	Outstanding
Slip Resistant	Yes
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com



TDS-0550-0614