

PRO TEX


STAIN PROOF FOR NATURAL STONE

DESCRIPTION

PROTEX is a solvent based impregnator for the protection of marble, granite and natural/artificial stone surfaces. Formulated with quality materials, the treatment protects the surface from water and oil based substances, without changing or altering the natural aspect of the stone material. Treatment penetrates into the surface pores without leaving any type of surface film or coating, allowing the stone to breathe. Non yellowing and UV resistant. Highly recommended as pre treatment on problematic materials, blocking any rising humidity and consequent appearance of salts.



CAN BE APPLIED WITH



SPRAYER, BRUSH, LAMBS WOOL, ROLLER

ADVANTAGES

- Stain resistant
- 98% permeable
- UV resistant
- Non yellowing

WHERE TO APPLY

For internal or external terracotta, marble, granite, structured ceramic and natural stones. For any material with medium/high absorbency.

USE

Product ready to use. Apply product in an abundant, uniform manner to dry and clean surfaces.

Apply uniformly by brush or spray. Remove any excess residues by clean cloth or buffer and allow surface to dry for 4-6 hours. If necessary, product can be used in conjunction with other surface finishes from Faber range.

Industrial inline applications: Apply product within the production line by immersion or by spray. On compact non porous materials, application can be carried out by roller or by sponge.

Pre treatment: before fixing or setting the material, apply product by spray, brush or immersion. Remove product excess by cloth and allow surface to dry. After 24 hrs proceed to fix treated material.

Also available: (see individual technical data sheet for product directions)
PRO TEX/LO: low odour, stain proof for natural stone

TECHNICAL DATA

ASPECT	: TRANSPARENT LIQUID
COLOUR - ODOUR	: COLOURLESS - ACETATE SOLVENT
PH (5% IN WATER)	: N/A
SPECIFIC GRAVITY (20°)	: 885 +/- 10 GR./LT
BIODEGRADABILITY	
FLASH POINT	: 23 ° C OPEN VASE

COVERAGE

10-15 SQM./LT (REFERRING TO ABSORPTION DEGREE OF THE MATERIAL)

PRE-CAUTIONS

DO NOT APPLY NEITHER ON OVERHEATED SURFACES NOR ON HUMID OR DIRT ONES .

SAFETY

R10 - F LAMMABLE
R66 - REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING
R67: VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS .
S2-KEEP OUT OF THE REACH OF CHILDREN
S25-AVOID CONTACT WITH EYES

STORAGE : KEEP THE CONTAINER CLOSED AND IN A COOL PLACE .

SHELF LIFE : 24 MONTHS IN THE ORIGINAL SEALED PACKING AND KEPT IN A COOL AND DRY PLACE .

PACKAGING : 1 LT. BOTTLES (12 PER CARTON) - 5 LT. CONTAINERS (4 PER CARTON)

ALTHOUGH THE INFORMATION ON THIS SHEET ARE THE RESULTS BOTH OF OUR RESEARCH AND OPERATIONAL TECHNICAL EXPERIENCE, THEY CANNOT BE CONSIDERED UNDERTAKING OR INVOLVE OUR RESPONSIBILITY AS THE CONDITIONS REQUIRED FOR THE APPLICATION CANNOT BE SUPERVISED BY US. FABER CHIMICA S.R.L. DOES NOT PROVIDE ANY WARRANTY, EITHER EXPRESS OR IMPLIED AND DOES NOT ASSUME ANY RESPONSIBILITY CONCERNING THE USE OF THESE DATA AND SUGGESTIONS.