

WS 800

DEEP PENETRATING WATER REPELLENT

DESCRIPTION

WS800 is a concentrated, solvent based general water repellent for stone and surfaces in general. Highly recommended as pre treatment of problematic material saving time on job site for surface clean ups from grout/cement residues. Economical, when compared to DREP or SOL170, high coverage, product guarantees an effective, long lasting protection, even after washing surfaces with acidic based substances. Low odour, product does not change or alter the natural aspect of the material.



CAN BE APPLIED WITH



BY IMMERSION, SPRAYER, BRUSH

ADVANTAGES

- Stain resistant
- High penetration
- UV resistant
- Non yellowing
- Breathable

WHERE TO APPLY

For internal or external terracotta, marble, granite, cement surfaces, tufo, porous stone in general.

USE

Product ready to use. Apply product in an abundant, uniform manner to dry and clean surfaces.

Apply uniformly by brush or spray. Remove any excess residues by clean cloth or buffer and allow surface to dry for 4-6 hours. If necessary, product can be used in conjunction with surface finishes from Faber range.

Pre treatment: before fixing or setting the material, apply product by spray, brush or immersion. Remove product excess by cloth and allow surface to dry. After 24 hrs proceed to fix treated material.

TECHNICAL DATA

ASPECT	: TRANSPARENT LIQUID
COLOUR - ODOUR	: COLOURLESS - MINERAL SOLVENT
PH (5% IN WATER)	: N/A
SPECIFIC GRAVITY (20°)	: 800 +/- 10 GR./LT
BIODEGRADABILITY	
FLASH POINT	: 30 ° C OPEN VASE

COVERAGE

8-15 SQM/LT (REFERRED TO PRODUCT APPLICATION ON THE VISIBLE SURFACE AND TO DILUTION)

PRE-CAUTIONS

DO NOT APPLY TO HEATED, DAMP OR DIRTY SURFACES

SAFETY



R10 - FLAMMABLE
R65 - HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED
R66 - REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING
S2 - KEEP OUT OF THE REACH OF CHILDREN
S23/24/25 - AVOID ANY INHALATION, CONTACT WITH SKIN AND EYES
S37 - WEAR SUITABLE GLOVES

STORAGE : KEEP THE CONTAINER CLOSED AND IN A COOL PLACE .

SHELF LIFE : 24 MONTHS IN THE ORIGINAL SEALED PACKING AND KEPT IN A COOL AND DRY PLACE .

PACKAGING : 1 LT. BOTTLES (12 PER CARTON) - 5 LT. CONTAINERS (4 PER CARTON) - 10 LT. CONTAINERS (IN BULK)

THOUGH THE INFORMATION ON THIS SHEET ARE THE RESULTS BOTH OF OUR RESEARCH AND OPERATIONAL TECHNICAL EXPERIENCE, THEY CANNOT BE CONSIDERED UNDERTAKING OR INVOLVE OUR RESPONSIBILITY AS THE CONDITIONS REQUIRED FOR THE APPLICATION CANNOT BE SUPERVISED BY US. FABER CHIMICA S.R.L. DOES NOT PROVIDE ANY WARRANTY, EITHER EXPRESS OR IMPLIED AND DOES NOT ASSUME ANY RESPONSIBILITY CONCERNING THE USE OF THESE DATA AND SUGGESTIONS.